### ҚАЗАҚСТАН РЕСПУБЛИКАСЫ ҰЛТТЫҚ ҒЫЛЫМ АКАДЕМИЯСЫНЫҢ

Қ. И. Сәтпаев атындағы Қазақ ұлттық техникалық зерттеу университеті

# ХАБАРЛАРЫ

# **ИЗВЕСТИЯ**

НАЦИОНАЛЬНОЙ АКАДЕМИИ НАУК РЕСПУБЛИКИ КАЗАХСТАН Казахский национальный исследовательский технический университет им. К. И. Сатпаева

### NEWS

OF THE ACADEMY OF SCIENCES OF THE REPUBLIC OF KAZAKHSTAN Kazakh national research technical university named after K. I. Satpayev

# SERIES OF GEOLOGY AND TECHNICAL SCIENCES

3 (435)

**MAY – JUNE 2019** 

THE JOURNAL WAS FOUNDED IN 1940

PUBLISHED 6 TIMES A YEAR



NAS RK is pleased to announce that News of NAS RK. Series of geology and technical sciences scientific journal has been accepted for indexing in the Emerging Sources Citation Index, a new edition of Web of Science. Content in this index is under consideration by Clarivate Analytics to be accepted in the Science Citation Index Expanded, the Social Sciences Citation Index, and the Arts & Humanities Citation Index. The quality and depth of content Web of Science offers to researchers, authors, publishers, and institutions sets it apart from other research databases. The inclusion of News of NAS RK. Series of geology and technical sciences in the Emerging Sources Citation Index demonstrates our dedication to providing the most relevant and influential content of geology and engineering sciences to our community.

Қазақстан Республикасы Ұлттық ғылым академиясы "ҚР ҰҒА Хабарлары. Геология және техникалық ғылымдар сериясы" ғылыми журналының Web of Science-тің жаңаланған нұсқасы Етегдіпд Sources Citation Index-те индекстелуге қабылданғанын хабарлайды. Бұл индекстелу барысында Clarivate Analytics компаниясы журналды одан әрі the Science Citation Index Ехрапиед, the Social Sciences Citation Index және the Arts & Humanities Citation Index-ке қабылдау мәселесін қарастыруда. Webof Science зерттеушілер, авторлар, баспашылар мен мекемелерге контент тереңдігі мен сапасын ұсынады. ҚР ҰҒА Хабарлары. Геология және техникалық ғылымдар сериясы Етегдіпд Sources Citation Index-ке енуі біздің қоғамдастық үшін ең өзекті және беделді геология және техникалық ғылымдар бойынша контентке адалдығымызды білдіреді.

НАН РК сообщает, что научный журнал «Известия НАН РК. Серия геологии и технических наук» был принят для индексирования в Emerging Sources Citation Index, обновленной версии Web of Science. Содержание в этом индексировании находится в стадии рассмотрения компанией Clarivate Analytics для дальнейшего принятия журнала в the Science Citation Index Expanded, the Social Sciences Citation Index и the Arts & Humanities Citation Index. Web of Science предлагает качество и глубину контента для исследователей, авторов, издателей и учреждений. Включение Известия НАН РК. Серия геологии и технических наук в Emerging Sources Citation Index демонстрирует нашу приверженность к наиболее актуальному и влиятельному контенту по геологии и техническим наукам для нашего сообщества.

### Бас редакторы

### э. ғ. д., профессор, ҚР ҰҒА академигі

### И.К. Бейсембетов

Бас редакторының орынбасары

Жолтаев Г.Ж. проф., геол.-мин. ғ. докторы

Редакция алкасы:

Абаканов Т.Д. проф. (Қазақстан)

Абишева З.С. проф., академик (Қазақстан)

Агабеков В.Е. академик (Беларусь)

Алиев Т. проф., академик (Әзірбайжан)

Бакиров А.Б. проф., (Кырғыстан)

Беспаев Х.А. проф. (Қазақстан)

Бишимбаев В.К. проф., академик (Қазақстан)

Буктуков Н.С. проф., академик (Қазақстан)

Булат А.Ф. проф., академик (Украина)

Ганиев И.Н. проф., академик (Тәжікстан)

Грэвис Р.М. проф. (АҚШ)

Ерғалиев Г.К. проф., академик (Қазақстан)

Жуков Н.М. проф. (Қазақстан)

Кожахметов С.М. проф., академик (Казахстан)

Конторович А.Э. проф., академик (Ресей)

Курскеев А.К. проф., академик (Қазақстан)

Курчавов А.М. проф., (Ресей)

Медеу А.Р. проф., академик (Қазақстан)

Мұхамеджанов М.А. проф., корр.-мүшесі (Қазақстан)

Нигматова С.А. проф. (Қазақстан)

Оздоев С.М. проф., академик (Қазақстан)

Постолатий В. проф., академик (Молдова)

Ракишев Б.Р. проф., академик (Қазақстан)

Сейтов Н.С. проф., корр.-мүшесі (Қазақстан)

Сейтмуратова Э.Ю. проф., корр.-мушесі (Қазақстан)

Степанец В.Г. проф., (Германия)

Хамфери Дж.Д. проф. (АҚШ)

Штейнер М. проф. (Германия)

### «КР ҰҒА Хабарлары. Геология мен техникалық ғылымдар сериясы».

ISSN 2518-170X (Online), ISSN 2224-5278 (Print)

Меншіктенуші: «Қазақстан Республикасының Ұлттық ғылым академиясы» РҚБ (Алматы қ.).

Қазақстан республикасының Мәдениет пен ақпарат министрлігінің Ақпарат және мұрағат комитетінде 30.04.2010 ж. берілген №10892-Ж мерзімдік басылым тіркеуіне қойылу туралы куәлік.

Мерзімділігі: жылына 6 рет.

Тиражы: 300 дана.

Редакцияның мекенжайы: 050010, Алматы қ., Шевченко көш., 28, 219 бөл., 220, тел.: 272-13-19, 272-13-18,

http://www.geolog-technical.kz/index.php/en/

© Қазақстан Республикасының Ұлттық ғылым академиясы, 2019

Редакцияның Қазақстан, 050010, Алматы қ., Қабанбай батыра көш., 69а.

мекенжайы: К. И. Сәтбаев атындағы геология ғылымдар институты, 334 бөлме. Тел.: 291-59-38.

Типографияның мекенжайы: «Аруна» ЖК, Алматы қ., Муратбаева көш., 75.

### Главный редактор

д. э. н., профессор, академик НАН РК

### И. К. Бейсембетов

Заместитель главного редактора

Жолтаев Г.Ж. проф., доктор геол.-мин. наук

Редакционная коллегия:

Абаканов Т.Д. проф. (Казахстан)

Абишева З.С. проф., академик (Казахстан)

Агабеков В.Е. академик (Беларусь)

Алиев Т. проф., академик (Азербайджан)

Бакиров А.Б. проф., (Кыргызстан)

Беспаев Х.А. проф. (Казахстан)

Бишимбаев В.К. проф., академик (Казахстан)

Буктуков Н.С. проф., академик (Казахстан)

Булат А.Ф. проф., академик (Украина)

Ганиев И.Н. проф., академик (Таджикистан)

Грэвис Р.М. проф. (США)

Ергалиев Г.К. проф., академик (Казахстан)

Жуков Н.М. проф. (Казахстан)

Кожахметов С.М. проф., академик (Казахстан)

Конторович А.Э. проф., академик (Россия)

Курскеев А.К. проф., академик (Казахстан)

Курчавов А.М. проф., (Россия)

Медеу А.Р. проф., академик (Казахстан)

Мухамеджанов М.А. проф., чл.-корр. (Казахстан)

Нигматова С.А. проф. (Казахстан)

Оздоев С.М. проф., академик (Казахстан)

Постолатий В. проф., академик (Молдова)

Ракишев Б.Р. проф., академик (Казахстан)

Сентов Н.С. проф., чл.-корр. (Казахстан)

Сейтмуратова Э.Ю. проф., чл.-корр. (Казахстан)

Степанец В.Г. проф., (Германия)

Хамфери Дж.Д. проф. (США)

Штейнер М. проф. (Германия)

#### «Известия НАН РК. Серия геологии и технических наук».

ISSN 2518-170X (Online),

**ISSN 2224-5278 (Print)** 

Собственник: Республиканское общественное объединение «Национальная академия наук Республики Казахстан (г. Алматы)

Свидетельство о постановке на учет периодического печатного издания в Комитете информации и архивов Министерства культуры и информации Республики Казахстан №10892-Ж, выданное 30.04.2010 г.

Периодичность: 6 раз в год Тираж: 300 экземпляров

Адрес редакции: 050010, г. Алматы, ул. Шевченко, 28, ком. 219, 220, тел.: 272-13-19, 272-13-18,

http://nauka-nanrk.kz/geology-technical.kz

© Национальная академия наук Республики Казахстан, 2019

Адрес редакции: Казахстан, 050010, г. Алматы, ул. Кабанбай батыра, 69а.

Институт геологических наук им. К. И. Сатпаева, комната 334. Тел.: 291-59-38.

Адрес типографии: ИП «Аруна», г. Алматы, ул. Муратбаева, 75

### Editor in chief

doctor of Economics, professor, academician of NAS RK

### I. K. Beisembetov

Deputy editor in chief

Zholtayev G.Zh. prof., dr. geol-min. sc.

Editorial board:

Abakanov T.D. prof. (Kazakhstan)

Abisheva Z.S. prof., academician (Kazakhstan)

Agabekov V.Ye. academician (Belarus)

Aliyev T. prof., academician (Azerbaijan)

Bakirov A.B. prof., (Kyrgyzstan)

Bespayev Kh.A. prof. (Kazakhstan)

Bishimbayev V.K. prof., academician (Kazakhstan)

**Buktukov N.S.** prof., academician (Kazakhstan)

**Bulat A.F.** prof., academician (Ukraine)

Ganiyev I.N. prof., academician (Tadjikistan)

Gravis R.M. prof. (USA)

**Yergaliev G.K.** prof., academician (Kazakhstan)

Zhukov N.M. prof. (Kazakhstan)

**Kozhakhmetov** S.M. prof., academician (Kazakhstan)

Kontorovich A.Ye. prof., academician (Russia)

**Kurskeyev A.K.** prof., academician (Kazakhstan)

Kurchavov A.M. prof., (Russia)

Medeu A.R. prof., academician (Kazakhstan)

Muhamedzhanov M.A. prof., corr. member. (Kazakhstan)

Nigmatova S.A. prof. (Kazakhstan)

**Ozdovev S.M.** prof., academician (Kazakhstan)

Postolatii V. prof., academician (Moldova)

**Rakishev** B.R. prof., academician (Kazakhstan)

**Seitov** N.S. prof., corr. member. (Kazakhstan)

Seitmuratova Ye.U. prof., corr. member. (Kazakhstan)

Stepanets V.G. prof., (Germany)

**Humphery G.D.** prof. (USA)

**Steiner M.** prof. (Germany)

### News of the National Academy of Sciences of the Republic of Kazakhstan. Series of geology and technology sciences.

ISSN 2518-170X (Online), ISSN 2224-5278 (Print)

Owner: RPA "National Academy of Sciences of the Republic of Kazakhstan" (Almaty)

The certificate of registration of a periodic printed publication in the Committee of information and archives of the

Ministry of culture and information of the Republic of Kazakhstan N 10892-Ж, issued 30.04.2010

Periodicity: 6 times a year Circulation: 300 copies

Editorial address: 28, Shevchenko str., of. 219, 220, Almaty, 050010, tel. 272-13-19, 272-13-18,

http://nauka-nanrk.kz/geology-technical.kz

© National Academy of Sciences of the Republic of Kazakhstan, 2019

Editorial address: Institute of Geological Sciences named after K.I. Satpayev

69a, Kabanbai batyr str., of. 334, Almaty, 050010, Kazakhstan, tel.: 291-59-38.

Address of printing house: ST "Aruna", 75, Muratbayev str, Almaty

### NEWS

### OF THE NATIONAL ACADEMY OF SCIENCES OF THE REPUBLIC OF KAZAKHSTAN

### SERIES OF GEOLOGY AND TECHNICAL SCIENCES

ISSN 2224-5278

Volume 3, Number 435 (2019), 96 – 101

https://doi.org/10.32014/2019.2518-170X.73

### Y. D. Zhaparkulova<sup>1</sup>, K. K. Anuarbekov<sup>1</sup>, K. E. Kaliyeva<sup>1</sup>, S. M. Abikenova<sup>1</sup>, A. Radzevicius<sup>2</sup>

<sup>1</sup>Kazakh national agrarian university, Almaty, Kazakhstan,
<sup>2</sup>Vytautas magnus university agriculture academy, Kaunas, Lietuva.
E-mail: ermekull@mail.ru, kanat.anuarbekov@kaznau.kz, karla\_3@mail.ru, salta\_84@inbox.ru, algirdas.radzevicius@asu.lt

# PURIFICATION DEGREES OF WASTE WATER UNDER DIFFERENT IRRIGATION REGIMES

**Abstract.** In the process of irrigation wastewater treatment is as its movement in the horizontal direction, and when leaking from top to bottom on the soil profile. In order to identify the degree of soil purification of wastewater, a complex of lysimetric studies was carried out in the territory of Almaty, Zhambyl and South Kazakhstan regions in various varieties of loamy soils.

**Key words:** lysimeters, aeration, biological uptake, wastewater, ingredients.

**Introduction.** Metal lysimeters had a height of 35, 65, 95, 155, 205 cm, and soil monoliths 30, 60, 90, 150, 200 cm. Lysimeters of small height (up to 1.5 m) were filled with monoliths of undisturbed structure, and more than 1.5 m - with soil of natural genetic structure with compaction close to natural. The inner surface of the lysimeters was covered with bitumen in 2 layers, filtered water through the pipe was sent to special containers. The lysimeters were planted with the same crops as for wastewater treatment and the irrigation regime was identical.

Comparison of the data of the chemical composition of the source water and filtration makes it possible to judge the degree of its purification.

The general quantitative and qualitative expression of the processes of absorption and migration of ingredients in waste water introduced into the soil with irrigation water had their regularities [1, 3].

Wastewater treatment occurred mainly in the zone of aeration, where he is actively in the process of nitrification, oxidation of proteins, cation exchange, biological uptake, etc. (table 1).

Sixty centimeter layer of soil, depending on the value of irrigation norms holds up to 100% of suspended solids, from 80 to 91% of nitrogen and from 90 to 99% of phosphorus.

Reducing the degree of purification soil of various ingredients can be found in the weakening at the end of the vegetation consumption of their higher vegetation, reducing the end of the vegetation consumption of their higher vegetation, reducing the microbiological activity of serozems, the relative "saturation" of the filter layer by the substances, changing the cationic composition of the arable horizon as a result of irrigation, meteorological conditions and other factors individually or in combination causing changes in the sorption properties of the soil.

Similar phenomena were observed in the crops of maize for silage in South Kazakhstan region (table 2). From mineral elements absorption of phosphorus was greater than the absorption of nitrogen. As irrigation rates increase, losses of nitrogen and phosphorus increase (table 3).

The absorption of the upper soil horizons decreases from irrigation to irrigation depending on the frequency of irrigation and water supply rate. Naturally, the greater the rate of water supply, the greater the flow of various organomineral substances. In this regard, the soil is oversaturated in a short period of inter-irrigation period does not have time to be completely exposed to various soil processes.

V.T.Dodolina noted that during the inter-irrigation period, part of the absorbed substances will be used by agricultural crops, and part under the influence of various processes is decomposed into simple compounds.

Table 1 – The degree of absorption of waste water ingredients by different soil layers, % (average loam) (on sugar beet crops)

# irrigation	Irrigation norm, m <sup>3</sup> /ha	Layer, cm	Suspended matter	HCO <sub>3</sub>	Cl	SO <sub>4</sub>	Ca	Mq	Na+K	N	P <sub>2</sub> O <sub>5</sub>
Option II (irrigation at 60% of the water pressure)											
1	700	0-30	50	40	50	40	40	40	42	60	50
		30-60	50	41	31	32,9	37	55	20	40	30
	Total	0-60	100	81	81	72,9	77	95	62	100	80
4	1100	0-30	50	39	40	50	39	40	45	50	45
		30-60	50	44	18	18	28	40	24	29	25
		60-90	-	7	22	22	19	20	15	1,0	6
	Total	0-90	100	90	80	90	86	100	84	80	76
Option III (irrigation at 70% of the water pressure)											
1	500	0-30	60	51	52	44	31	50	50	58	51
		30-60	40	45	30	45	69	36	38	34	28
	Total	0-60	100	96	82	89	100	86	88	92	79
7	800	0-30	60	40	10	30	24	44	40	49	46
		30-60	40	18	10	30	12	16	10	30	19
		60-90	-	28	50	21	17	36	36	17	25
	Total	0-90	100	86	70	81	53	96	86	96	90
		Op	otion IV (irrigat	ion at 80%	of the w	ater press	ure)				
1	400	0-30	55	49	68	40	27	60	55	63	58
		30-60	45	43	20	51	68	28	39	35	33
	Total	0-60	100	92	88	91	95	88	94	98	91
10	650	0-30	40	30	10	25	10	30	41	40	46
		30-60	50	16	18	14	22	10	6	29	15
		60-90	10	43	55	39	34	60	41	31	31
	Total	0-90	100	89	83	78	66	100	88	100	92

Table 2 – Degrees of wastewater treatment by different soil layers on maize crops for silage (SKR)

Soil layer,	Norm of watering,	Ingredients, mg/l							
cm	m³/ha	HCO <sub>3</sub>	Cl	$SO_4$	Ca	Mq	Na+ K		
0-30	700	120,7	19,8	72,6	31,2	11,6	50,4		
0-30	900	131,3	21,2	74,3	31,8	12,6	53,4		
30-60	700	96,4	11,4	34,3	10,5	6,3	20,5		
30-60	900	87,2	10,1	32,6	9,9	6,0	18,7		
60-100	700	14,6	6,2	18,9	5,3	2,8	7,2		
60-100	900	12,3	5,9	16,2	5,4	2,4	6,6		
Source water		235,0	36,51	174,2	77,0	20,4	102,0		

Table 3 – Absorption of N, P, K in different soil layers

Performances	In layer, cm	Norms of watering, mm								
Performances		400	500	600	700	800	900	1000		
Phosphorus	0-30	61	58	60	50	41	56	50		
Nitrogen	0-30	58	51	50	50	46	48	50		
Phosphorus	0-90	99	93	92	90	91	79	79		
Nitrogen	0-90	91	80	88	86	80	65	70		

The longer the inter-irrigation period, the higher the absorbing capacity of the soil, and hence the degree of purification.

Research materials and the above data show that on gray soils with deep groundwater, irrigation with a moisture threshold, 70% water norm provides not only high yields, but also an appropriate degree of soil post-treatment in the root layer.

In Almaty region were laid lysimeters depth of 1.5; 2, 3 meters.

Experimental data showed that at a depth of 1.5 m the filtrate was almost clean, and at a depth of 3.0 no changes in soil moisture were observed.

Therefore, while maintaining the optimal irrigation regime and its observance, wastewater does not affect the depth of more than 3 m [2, 4-7].

**Methods.** Under conditions of irrigation with wastewater, the following agrotechnical indicator is effective in substantiating the optimal values of irrigation rates and the dose of fertilizers on all types of soil: chemical composition (N, P, K content) of main and by-products; removal of elements of the mineral nutrition of the harvest unit; soil availability with nitrogen, phosphorus, potassium and microelements permissible for plants: use of fertilizers from the soil by field crops depending on the soil type, weather conditions and the level of specified crops; payback of 1 kg N, P, K. Therefore, the correct determination of the irrigation rates and the dose of fertilizers calculated for the programmed level of the crop is one of the most important elements of the entire ecosystem under consideration.

In order to use the technique in question, it is necessary first of all to calculate the "B" removal of the corresponding mineral nutrient elements with a programmed yield. Knowing the level of the yield programmed at this stage (where  $Y_0$  is the programmable yield of the main product, centners per hectare), and having the ratio of main production and secondary production  $(Y_n)$ , it is easy to make the removal of nutrients using the ratio:

$$B_0 = Y_0 \cdot C_0 + Y_n \cdot C_n \,, \tag{1}$$

where  $C_0$  – nutrient content per unit of main product (kg/c);  $C_n$  – nutrient content per unit of by-product (kg/c);  $Y_n$  – by-products of the programmable crop, which is determined by the formula;

$$Y_n = \alpha \cdot Y_0. \tag{2}$$

Here is  $\alpha$  – coefficient that takes into account the ratio of the main product to the by - product (for corn – 2.8, perennial grasses – 0, barley – 1.1, winter wheat – 1.4).

The amount of expected receipt of mineral substances with waste water is determined by the formula:

$$N_m = \alpha \cdot M/100; P_m = \varphi \cdot M/1000; K_n = k \cdot M/1000,$$
 (3)

where  $N_m$ ,  $P_m$ ,  $K_n$  – the amount of expected intake of nitrogen, phosphorus and potassium, kg/ha;  $\alpha$ ,  $\varphi$ , k – content of nitrogen, phosphorus and potassium, mg/l.

Possible removal of the input mineral substances with waste water is determined from the following expressions:

$$N_{vn} = N_m \cdot \alpha_n; \tag{4}$$

$$P_{\nu n} = P_m \cdot \alpha_{\omega}; \tag{5}$$

$$K_{vn} = K_m \cdot \alpha_k, \tag{6}$$

where  $N_{yn}$ ,  $P_{yn}$ ,  $K_{yn}$  – possible removal of nitrogen, phosphorus and potassium with a yield of incoming mineral substances with waste water (kg/ha);  $\alpha_n$ ,  $\alpha_{\varphi}$ ,  $\alpha_k$  – utilization rate of nitrogen, phosphorus and potassium from wastewater.

The amount of nitrogen, phosphorus and potassium used from the soil is calculated by the formula:

$$N_{vp} = N_p \cdot \alpha_{np}; \tag{7}$$

$$P_{vp} = P_p \cdot \alpha_{op}; \tag{8}$$

$$K_{vp} = K_p \cdot \alpha_{kp},\tag{9}$$

where  $N_{yp}$ ,  $P_{yp}$ ,  $K_{yp}$  – nitrogen, phosphorus and potassium content in soil, kg/100;  $N_p$ ,  $P_p$ ,  $K_p$  – amount of nitrogen, phosphorus and potassium used by plants from the soil;  $\alpha_{np}$ ,  $\alpha_{\varphi p}$ ,  $\alpha_{kp}$  – utilization rate of nitrogen, phosphorus and potassium from soil.

At the same time, the need for mineral fertilizers should be decided in each case, based on the following definitions:

1. If the amount of nitrogen, phosphorus and potassium used from the soil and wastewater is less than the removal of these nutrients by crop products, i.e.,

$$B_N > N_{\nu p} + N_{\nu n} \,; \tag{10}$$

$$B_p > P_{\nu p} + P_{\nu n}; \tag{11}$$

$$B_k > K_{vp} + K_{vn}. \tag{12}$$

Then mineral fertilizers are made from the calculation of compensation of the differences.

2. If the amount of nitrogen, phosphorus and potassium used from the soil and wastewater is greater than or one of them is greater than the removal of these nutrients by the crop production, i.e.,

$$B_N < N_{\nu p} + N_{\nu n} \,; \tag{13}$$

$$B_p < P_{\nu p} + P_{\nu n}; \tag{14}$$

$$B_k < K_{vp} + K_{vn}. \tag{15}$$

Then the irrigation rate of crops is determined by the maximum value of the nutrient removal of one of the nutrients and mineral fertilizers are taken out of the calculation of compensation for the deficiency of other nutrients.

Irrigation norm of agricultural crops under irrigation by sewage is calculated by the formula:

$$M_{na} = [B(NPK)i - P(NPK)i] \cdot 100/\alpha_i, \qquad (16)$$

where  $M_{na}$  – irrigation norm of agricultural crops taking into account the fertilizer value of waste water, m³/ha; B(NPK)i – removal of the 1st nutrient element by agricultural products; P(NPK)i – use of the 2nd nutrient element from the soil;  $\alpha_i$  – utilization rate of the 3rd nutrient element from wastewater.

If  $M_{na} < M$  then, the necessity of extra amount of water, compensating the deficiency of water consumption of agricultural crops, i.e.:

$$\Delta M = M - M_{na},\tag{17}$$

where  $\Delta M$  – additional rate of supply of irrigation water to compensate the water deficit of agricultural crops.

Consequently, one of the main tasks in the use of wastewater for irrigation is to determine the share of irrigation water in the water deficit, providing optimal water-salt and food regime of the soil and high crop yields.

For the participation of irrigation water in the deficit of water consumption of agricultural crops in irrigation with waste ater is determined by the formula:

$$\alpha_c = I - \frac{B(NPK)i - P(NPK)i}{\alpha_i \cdot M} \cdot 100. \tag{18}$$

Thus, the account of nutrients content in waste water provides a normal natural regime of the soil and economical to the introduction of these elements in the form of fertilizers.

Thus, the following should be taken into account when establishing the irrigation regime for wastewater irrigation:

In some (critical) periods of vegetation, crops may be unsatisfactory inflow of wastewater. Additional irrigation from natural water bodies – rivers, reservoirs or groundwater-can be used to replenish this moisture deficit.

The amount of additional water needed to cover the water shortage is found by the formula:

$$M_a = W_w - Q_{ad} \cdot T_k, \tag{19}$$

 $W_w$  – the need of the culture in water for the critical period, m<sup>3</sup>/ha;  $Q_{ad}$  – average daily consumption of wastewater coming from the city, m<sup>3</sup>/ha;  $T_k$  – the duration of the critical period in days.

In the practice of designing wastewater treatment, such periods are established by comparing the crop irrigation hydraulic module in the crop rotation (q in l/sec per 1 ha) with the wastewater supply hydraulic module determined by the formula:

$$q_1 = \frac{Q_{ad}}{86,4 \cdot \omega}, \frac{l}{cek},\tag{20}$$

where  $Q_{ad}$  – average daily waste water consumption, m<sup>3</sup>/day;  $\omega$  – area of simultaneous irrigation, ha.

When establishing irrigation and irrigation standards, it is necessary to take into account the cleaning capacity of the soil. It is known that during irrigation and subsequent movement of waste water on the surface and on the profile of the soil, their intensive purification occurs due to the mechanical, molecular sorption, ion-sorption, chemical and biological absorption capacity of the soil. The effect of soil purification decreases with increasing water supply rates. On loamy soils of the southern zone of Kazakhstan, intensive cleaning occurs at irrigation rates up to 600 mm, and at a rate of 900 mm and more, the soil will not give a cleaning effect.

**Results.** Each soil is characterized by a certain absorption capacity. The larger it is, the higher the degree of wastewater treatment. For example, loamy soils of Zhambyl, South Kazakhstan and Almaty regions have high absorption capacity. In the meter layer of these soils, on average, 60 to 90% of the elements of mineral nutrition are retained.

As irrigation rates increase, the number of irrigations and the capacity of the soil filter layer decrease will be less pronounced.

By the end of the growing season and subsequent years of irrigation, the absorption capacity of the soil is somewhat reduced. This is due to the fact that the soil with long-term irrigation is oversaturated with substances brought with wastewater and its cleaning ability is gradually reduced. Therefore, it is very important to maintain a balance between the flow of waste water ingredients and their use by plants.

One of the reasons for the "fatigue" of the soil of irrigation fields is the overload of soil with irrigation water both during the growing season and during the non-vegetation period. As a result of the overload in the soil, the processes of transformation of substances can not proceed normally, soil fertility is ensured.

For the correct use of waste water must necessarily take into account the water-holding capacity of the soil. For wastewater treatment, the amount of runoff should be zero. Water supplied in excess of the water-holding capacity of the soil enters the groundwater.

The smaller the irrigation rate and the longer the irrigation time, the greater the difference between the inflow and outflow of wastewater. The irrigation rate should be calculated so that it does not exceed the permissible ultra-precise value of the intensity of infiltration of irrigation water and the permissible depth of the groundwater level. The value of infiltration and groundwater reaches its peak in the spring, during the snowmelt. It is, all other things being equal, on average twice as much as the growing season, when water is expended heavily on evaporation and transpiration by vegetation. Therefore, the annual irrigation rate should be sufficiently consistent with the conditions of underground outflow of groundwater, to ensure the possibility of neutralization and treatment of waste water in the infiltration process, also fully take into account the needs of plants in moisture. In order to reduce winter irrigation norms, it is necessary to organize irrigation of the entire area of irrigation fields.

The basis of the year-round irrigation cycle for wastewater treatment should be the satisfaction of the crop with moisture during the growing season and the accumulation of essential nutrients in the soil during the growing season.

The basis of the irrigation regime should be the creation of a predominant downward current, providing leaching of salts from the upper horizons of the soil. There was no danger of soil alkolining, for which the amount applied with wastewater and in the form of calcium fertilizer was greater than the amount applied with wastewater sodium. Because of this, when calculating the irrigation regime, it is necessary to observe the balance:

- a) nutrients from wastewater;
- b) moisture:
- c) water-soluble salts.

Of the above, the most important is the provision of water to plants, which is crucial in the formation of the basis of the future harvest, especially in the southern regions of the country and the balance of water-soluble salts, which remain in large quantities after treatment facilities.

Irrigation regime of agricultural crops of wastewater treatment should consist of vegetation and non-vegetation irrigation regimes.

The basis of irrigation regime of vegetation irrigation should be based on the same principles as in conventional irrigation.

### Е. Д. Жапаркулова<sup>1</sup>, К. К. Ануарбеков<sup>1</sup>, К. Е. Калиева<sup>1</sup>, С. М. Абикенова<sup>1</sup>, Р. Алгирдас<sup>2</sup>

<sup>1</sup>Қазақ ұлттық аграрлық университеті, Алматы, Қазақстан, <sup>2</sup>Витаутас Магнус ауылшаруашылық академиясы, Каунас, Литва

### **ӘРТҮРЛІ СУҒАРУ РЕЖИМІ КЕЗІНДЕГІ ТӨГІНДІ СУЛАРДЫ ТАЗАРТУ ДӘРЕЖЕСІ**

**Аннотация.** Суғару процесі кезінде төгінді суларды тазарту көлденең бағытта, топырақ профилі бойынша жоғарыдан төмен қарай жүреді. Алматы, Жамбыл және Оңтүстік Қазақстан облыстарының аумағында топырақты төгінді сулардан тазарту дәрежесін анықтау мақсатында саздақ топырақтардың әртүрлі сорттарында лизиметрлік зерттеу кешені жүргізілді.

Түйін сөздер: лизиметр, аэрация, биологиялық жұту, төгінді сулар, ингредиенттер.

### Е. Д. Жапаркулова<sup>1</sup>, К. К. Ануарбеков<sup>1</sup>, К. Е. Калиева<sup>1</sup>, С. М. Абикенова<sup>1</sup>, Р. Алгирдас<sup>2</sup>

<sup>1</sup>Казахский национальный аграрный университет, Алматы, Казахстан, <sup>2</sup>Витаутас Магнус сельскохозяйственная академия, Каунас, Литва

### СТЕПЕНЬ ОЧИСТКИ СТОЧНЫХ ВОД ПРИ РАЗЛИЧНЫХ РЕЖИМАХ ОРОШЕНИЯ

**Аннотация.** В процессе полива очистка сточных вод происходит как при ее движении в горизонтальном направлении, так и при протекании сверху вниз по профилю почвы. С целью выявления степени очистки почвы от сточных вод на территории Алматинской, Жамбылской и Южно-Казахстанской областей в различных сортах суглинистых почв был проведен комплекс лизиметрических исследований.

Ключевые слова: лизиметры, аэрация, биологическое поглощение, сточные воды, ингредиенты.

### Information about authors:

Zhaparkulova Yermekkul, candidate technical science, assos. Professorof the Department of "Water resources and melioration", Kazakh national agrarian university; ermekull@mail.ru; https://orcid.org/0000-0002-5593-0016

Anuarbekov Kanat, PhD doctor, senior lecturer of the Department of "Water resources and melioration", Kazakh national agrarian university; kanat.anuarbekov@kaznau.kz; https://orcid.org/0000-0003-0832-6980

Kaliyeva Karlygash, PhD student, Kazakh national agrarian university; karla\_3@mail.ru; https://orcid.org/0000-0001-5723-2644

Abikenova Saltanat, PhD doctor, senior lecturer of the Department of "Water resources and melioration", Kazakh national agrarian university; salta 84@inbox.ru; https://orcid.org/0000-0001-7786-741X

Radzevicius Algirdas, Dr. techn. sci., Professor, Aleksandras stulginskis university, AkademijaKauno r., Lithuania; algirdas.radzevicius@asu.lt; https://orcid.org/0000-0003-4124-0388

### REFERENCES

- [1] Shulz M. Year-round irrigation with wastewater. M.: Kolos, 1965.
- [2] Anuarbekov K., Zubairov O., Nusipbekov M. Improving water-salt regime in irrigated agriculture // Life Science Journal. 2014. 11(5), P. 459-464. ISSN 1097-8135.
  - [3] Kanardov I.P. Use of wastewater for irrigation. Rosselchozizdat, 1977.
- [4] Anuarbekov K.K and other. Water-saving technology of irrigation of corn // Journal News of the National academy of sciences of the Republic of Kazakhstan. Series of Geology and Technical Sciences. 2018. Vol. 2, N 428. P. 149-155.
- [5] Anuarbekov K.K. and other. Exploitation of wastewater irrigation system (WWIS) // News of the National academy of sciences of the Republic of Kazakhstan. Series of Geology and Technical Sciences. 2018. Vol. 6, N 432. P. 129-136. ISSN 2224-5278. https://doi.org/10.32014/2018.2518-170X.43
- [6] Anuarbekov K.K., Zubairov O.Z., Nusipbekov M.Z. Influence of the improvement of water-salt regime on the yield // Biosciences Biotechnology Research Asia. April 2015. Vol. 12(1). P. 999-1006.
- [7] Alimbayev Y.N., Anuarbekov K.K., Kalybekova E.M., Sagaev A.A., Zhailaubaeva M.M. Improvement of the ecological meliorative state of the irrigated lands in the lower course of the Syr Darya // International Journal of Pharmacy & Technology. Dec-2016. Vol. 8. Issue 4. P. 27143-27157.

# Publication Ethics and Publication Malpractice in the journals of the National Academy of Sciences of the Republic of Kazakhstan

For information on Ethics in publishing and Ethical guidelines for journal publication see http://www.elsevier.com/publishingethics and http://www.elsevier.com/journal-authors/ethics.

Submission of an article to the National Academy of Sciences of the Republic of Kazakhstan implies that the described work has not been published previously (except in the form of an abstract or as part of a published lecture or academic thesis electronic preprint, or as an see http://www.elsevier.com/postingpolicy), that it is not under consideration for publication elsewhere, that its publication is approved by all authors and tacitly or explicitly by the responsible authorities where the work was carried out, and that, if accepted, it will not be published elsewhere in the same form, in English or in any other language, including electronically without the written consent of the copyrightholder. In particular, translations into English of papers already published in another language are not accepted.

No other forms of scientific misconduct are allowed, such as plagiarism, falsification, fraudulent data, incorrect interpretation of other works, incorrect citations, etc. The National Academy of Sciences of the Republic of Kazakhstan follows the Code of Conduct of the Committee on Publication Ethics (COPE), and follows the COPE Flowcharts for Resolving Cases of Suspected Misconduct (<a href="http://publicationethics.org/files/u2/New\_Code.pdf">http://publicationethics.org/files/u2/New\_Code.pdf</a>). To verify originality, your article may be checked by the Cross Check originality detection service <a href="http://www.elsevier.com/editors/plagdetect">http://www.elsevier.com/editors/plagdetect</a>.

The authors are obliged to participate in peer review process and be ready to provide corrections, clarifications, retractions and apologies when needed. All authors of a paper should have significantly contributed to the research.

The reviewers should provide objective judgments and should point out relevant published works which are not yet cited. Reviewed articles should be treated confidentially. The reviewers will be chosen in such a way that there is no conflict of interests with respect to the research, the authors and/or the research funders.

The editors have complete responsibility and authority to reject or accept a paper, and they will only accept a paper when reasonably certain. They will preserve anonymity of reviewers and promote publication of corrections, clarifications, retractions and apologies when needed. The acceptance of a paper automatically implies the copyright transfer to the National Academy of Sciences of the Republic of Kazakhstan.

The Editorial Board of the National Academy of Sciences of the Republic of Kazakhstan will monitor and safeguard publishing ethics.

Правила оформления статьи для публикации в журнале смотреть на сайте:

www:nauka-nanrk.kz

ISSN 2518-170X (Online), ISSN 2224-5278 (Print)

http://www.geolog-technical.kz/index.php/en/

Верстка Д. Н. Калкабековой

Подписано в печать 11.06.2019. Формат 70х881/8. Бумага офсетная. Печать – ризограф. 15,7 п.л. Тираж 300. Заказ 3.